




CABLE SPECIFICATION

Issued: October 7, 2010

Revised: August 9, 2011



ITEM: 30-002-76M-RYNONP

Fiber Diameter (core/clad)	microns	8.3/125**
Fiber Type	Singlemode	Step Index
Numerical Aperture	--	0.13
Maximum Attenuation @ 1310/1550nm	dB/km	≤0.40/0.30
Number of Fibers	--	2
Buffer Diameter	microns	900
Storage Temperature Range	°C	-40 to +85
Operating Temperature Range	°C	-20 to +85
Max. Tensile Load for Installation	N (lbf)	1000 (225)
Max. Tensile Load, Long-Term	N (lbf)	500 (112)
Min. Bend Radius, Unloaded	--	10 X O.D.
Crush Resistance (EIA 455-41)	N/cm	100
Impact Resistance (EIA 455-25)	Impacts	25
Flexing, ±90° (EIA 455-104)	Cycles	25
Cable Outside Diameter, Nom.	mm (in.)	2.9 X 6.0(0.114 x 0.235)
Cable Weight, Nom.	kg/km (lbs./1000)	18 (12)

DESCRIPTION: 2 tight-buffered fibers, aramid yarns, Yellow plenum rated Remguard™ outer jacket in a zip cord construction, OFNP C(ETL)US.

**ITU G.652b

**Note: The values listed herein are nominal. Remeewire and cable reserves the right to modify.*